



TOYOTA CORONA MARK II

Deluxe Station Wagon



Fully padded instrument panel with recessed gauges.



Full-reclining bucket seats.



Flat-floored cargo space with wall-to-wall carpet.



Combination ignition switch/steering lock.



Windscreen wiper/washer control knob



Folding rear seat roomy enough for three adults.

Superior means TOYOTA... Now—The new Corona Mark II Deluxe Station Wagon!

What keeps Toyota on top is superior quality, great engineering and dedication to excellence. Our cars have won a world-wide reputation the hard way, in millions of miles of use. Now we present an all-new luxury station wagon. The Corona Mark II Deluxe Station Wagon is bigger—longer, lower, wider, a four-door family wagon that offers more motoring pleasure. Among the many new features are: An extra powerful 1.6 litre OHC-4 92 HP engine; Fully padded instrument panel with Hi-Fi radio; Full-reclining bucket seats covered in ventilation perforated vinyl leatherette; Wall-to-wall carpet; Flat-floored cargo space... they're all available at no extra cost! Look over these exciting new station wagons at your nearest Toyota dealer's!

SPECIFICATIONS

ENGINE: Water-cooled, 4-cylinder in-line, SOHC, 1591 c.c. Bore 86 mm. (3.39 in.), stroke 68.5 mm. (2.70 in.). Compression ratio 8.5 to 1. Max. output (SAE) 92 HP at 5500 rpm. Max. torque (SAE) 13.5 m.-kg. (98 ft./lb.) at 3800 rpm. 12-volt 40 amp.hr. battery, 12-volt 480-watt alternator. Down-draft, two-barrel carburettor with automatic choke. Fuel tank capacity 52 litres (11.4 Imp. gal.). Full pressure force-feed type lubrication with full-flow type oil filter.

CLUTCH: Single dry plate and diaphragm spring with hydraulic actuation.

TRANSMISSION: 4-speed gearbox. All 4 forward gears synchromesh. Ratios—1st 3.673, 2nd 2.114, 3rd 1.403, top 1.000, reverse 4.183. Shift lever mounted on centre floor. Final reduction gear ratio 4.375 to 1.

SUSPENSION: Front: Independent with coil springs and wishbones. Rear: Asymmetrical semi-elliptical leaf springs. Double-acting hydraulic shock absorbers front and rear. Torsion-bar stabilizer in front.

BRAKES: Foot brake operates hydraulically on all wheels. Front disc brakes with vacuum booster and pressure control valve. Rear drum brakes with leading and trailing shoes. Parking brake operates mechanically on rear wheels.

STEERING: Recirculating ball type gearbox. Ratio 19.5 to 1. Turning circle 9.7 meters (31.8 ft.).

WHEELS AND TYRES: Pressed steel disc wheels. 6.45-13 4PR tyres.

DIMENSIONS AND WEIGHT: Wheelbase 2510 mm. (98.8 in.). Overall length 4320 mm. (170.1 in.). Overall height 1425 mm. (56.1 in.). Overall width 1605 mm. (63.2 in.). Tread, front 1325 mm. (52.2 in.), rear 1320 mm. (52.0 in.). Ground clearance 170 mm. (6.7 in.). Kerb weight 1045 kg. (2305 lb.).

PERFORMANCE: Max. speed 145 km/hr. (90 mph). Max. cruising speed 125 km/hr. (78 mph).

*Toyota Motor reserves the right to alter prices, and any details of specifications and equipment without notice. Details of specifications and equipment are also subject to change to suit local conditions and requirements.

*Please inquire at your local dealer's for details and availability of local equipment.